






TECHNICAL DATA SHEET - CST 0130/01 - 23/09/2013

GF 7700

| | | | | |
|-----|-----|---|---|---|
| (*) | |  |  |  |
| T | °C | -200 +280 | | |
| p | bar | | 200 | 50 |
| V | m/s | | 2 | 25 |
| pH | | 0 + 14 | | |



Avoid the product's use at the maximum temperature and pressure associated values without consult the manufacturer

Composition

-100% GFO® GORE yarns

Features

This packing is made by GFO® GORE yarns. The advantage of this yarn is to combine the benefits of PTFE and graphite. The graphite is encapsulated inside the expanded PTFE.

The packing is marked 100% GFO®

Applications

Packing specific for pump services.

GF7700 GFO® it's an excellent packing for all industrial sealing services except the strong oxidizers.

| size mm | size inch | kg/box | lbs/box | mt/box | ft/box | mt/kg | ft/lbs |
|---------|-----------|--------|---------|--------|--------|-------|--------|
| 3,0 | 1/8 | 1,0 | 2,2 | 74,1 | 243 | 74,1 | 110,3 |
| 4,0 | - | 1,0 | 2,2 | 41,7 | 137 | 41,7 | 62,1 |
| 5,0 | 3/16 | 1,0 | 2,2 | 26,7 | 87 | 26,7 | 39,7 |
| 6,0 | - | 2,5 | 5,5 | 46,3 | 152 | 18,5 | 27,6 |
| 6,5 | 1/4 | 2,5 | 5,5 | 39,4 | 129 | 15,8 | 23,5 |
| 8,0 | 5/16 | 2,5 | 5,5 | 26,0 | 85 | 10,4 | 15,5 |
| 9,5 | 3/8 | 2,5 | 5,5 | 18,5 | 61 | 7,4 | 11,0 |
| 10,0 | - | 2,5 | 5,5 | 16,7 | 55 | 6,7 | 9,9 |
| 11,0 | 7/16 | 2,5 | 5,5 | 13,8 | 45 | 5,5 | 8,2 |
| 12,0 | - | 2,5 | 5,5 | 11,6 | 38 | 4,6 | 6,9 |
| 12,7 | 1/2 | 2,5 | 5,5 | 10,3 | 34 | 4,1 | 6,2 |
| 14,0 | 9/16 | 5,0 | 11,0 | 17,0 | 56 | 3,4 | 5,1 |
| 16,0 | 5/8 | 5,0 | 11,0 | 13,0 | 43 | 2,6 | 3,9 |
| 17,5 | 11/16 | 5,0 | 11,0 | 10,9 | 36 | 2,2 | 3,2 |
| 18,0 | - | 5,0 | 11,0 | 10,3 | 34 | 2,1 | 3,1 |
| 19,0 | 3/4 | 5,0 | 11,0 | 9,2 | 30 | 1,8 | 2,8 |
| 22,0 | 7/8 | 5,0 | 11,0 | 6,9 | 23 | 1,4 | 2,1 |
| 25,5 | 1 | 5,0 | 11,0 | 5,1 | 17 | 1,0 | 1,5 |

Packaged +/- 10 % in weight.
Customized sizes and packaging are available on demand