






TECHNICAL DATA SHEET - CST 0131/03 - 24/09/2013

GL 7000

(*)				
T	°C	-200 +280		
p	bar		200	50
V	m/s		2	25
pH		0 + 14		



Avoid the product's use at the maximum temperature and pressure associated values without consult the manufacturer

Composition

- ePTFEg yarns

Features

The packing GL7000 is made by high strength ePTFE yarns filled with graphite powder and silicon lubricant.

Applications

Packing suitable for reciprocating and centrifugal pumps. Avoid the strong oxidizers

size mm	size inch	kg/box	lbs/box	mt/box	ft/box	mt/kg	ft/lbs
3,0	1/8	1,0	2,2	69,4	228	69,4	103,4
4,0	-	1,0	2,2	39,1	128	39,1	58,2
5,0	3/16	1,0	2,2	25,0	82	25,0	37,2
6,0	-	2,5	5,5	43,4	142	17,4	25,9
6,5	1/4	2,5	5,5	37,0	121	14,8	22,0
8,0	5/16	2,5	5,5	24,4	80	9,8	14,5
9,5	3/8	2,5	5,5	17,3	57	6,9	10,3
10,0	-	2,5	5,5	15,6	51	6,3	9,3
11,0	7/16	2,5	5,5	12,9	42	5,2	7,7
12,0	-	2,5	5,5	10,9	36	4,3	6,5
12,7	1/2	2,5	5,5	9,7	32	3,9	5,8
14,0	9/16	5,0	11,0	15,9	52	3,2	4,7
16,0	5/8	5,0	11,0	12,2	40	2,4	3,6
17,5	11/16	5,0	11,0	10,2	33	2,0	3,0
18,0	-	5,0	11,0	9,6	32	1,9	2,9
19,0	3/4	5,0	11,0	8,7	28	1,7	2,6
22,0	7/8	5,0	11,0	6,5	21	1,3	1,9
25,5	1	5,0	11,0	4,8	16	1,0	1,4
Packaged+/- 10 % in weight. Customized sizes and packaging are available on demand							