






TECHNICAL DATA SHEET - CST 0151/02 - 03/09/2007

GL 7600K

(*)			
T	°C	-100 / +250	
p	bar	250	50
V	m/s	3	25
pH	3 ÷ 12		

(*) Avoid the product's use at the maximum temperature and pressure associated values without consult the manufacturer

Composition

- Aramid yarns
- ePTFE graphitized yarns

Features

Gland packing manufactured with ePTFE graphitized yarns and Aramid yarns with a particular braiding process. This design increases the resistance to extrusion and preserves the shaft's wear.

Applications

Gland packing for centrifugal and reciprocating pumps, agitators, mixers, suitable with the main industrial fluids and water.

size mm	size inch	kg/box	lbs/box	mt/box	ft/box	mt/kg	ft/lbs
3,0	1/8	1,0	2,2	74,1	243	74,1	110,3
4,0	-	1,0	2,2	41,7	137	41,7	62,1
5,0	3/16	1,0	2,2	26,7	87	26,7	39,7
6,0	-	2,5	5,5	46,3	152	18,5	27,6
6,5	1/4	2,5	5,5	39,4	129	15,8	23,5
8,0	5/16	2,5	5,5	26,0	85	10,4	15,5
9,5	3/8	2,5	5,5	18,5	61	7,4	11,0
10,0	-	2,5	5,5	16,7	55	6,7	9,9
11,0	7/16	2,5	5,5	13,8	45	5,5	8,2
12,0	-	2,5	5,5	11,6	38	4,6	6,9
12,7	1/2	2,5	5,5	10,3	34	4,1	6,2
14,0	9/16	5,0	11,0	17,0	56	3,4	5,1
16,0	5/8	5,0	11,0	13,0	43	2,6	3,9
17,5	11/16	5,0	11,0	10,9	36	2,2	3,2
18,0	-	5,0	11,0	10,3	34	2,1	3,1
19,0	3/4	5,0	11,0	9,2	30	1,8	2,8
22,0	7/8	5,0	11,0	6,9	23	1,4	2,1
25,5	1	5,0	11,0	5,1	17	1,0	1,5
packaged +/- 10 % in weight							