






TECHNICAL DATA SHEET - CST 0160/03 - 23/06/2014

K6600C

(*)				
T	°C	-100 +280		
p	bar		100	25
V	m/s		3	10
pH		3 ÷ 12		

(*) Avoid the product's use at the maximum temperature and pressure associated values without consult the manufacturer

Average Composition

- Continuous aramid yarns
- PTFE impregnation
- Lubricant silicon free

Features

This packing is made from continuous thermostable aramid yarns.
Each yarn is impregnated with PTFE dispersion and silicon free inert lubricant.

Applications

Suitable for use on centrifugal and piston pumps with very abrasive fluids. Low shaft's speed or shaft's protection is needed.

sezione mm	sezione inch	kg/box	lbs/box	mt/box	ft/box	mt/kg	ft/lbs
3,0	1/8	1,0	2,2	74,1	243	74,1	110,3
4,0	-	1,0	2,2	41,7	137	41,7	62,1
5,0	3/16	1,0	2,2	26,7	87	26,7	39,7
6,0	-	2,5	5,5	46,3	152	18,5	27,6
6,5	1/4	2,5	5,5	39,4	129	15,8	23,5
8,0	5/16	2,5	5,5	26,0	85	10,4	15,5
9,5	3/8	2,5	5,5	18,5	61	7,4	11,0
10,0	-	2,5	5,5	16,7	55	6,7	9,9
11,0	7/16	2,5	5,5	13,8	45	5,5	8,2
12,0	-	2,5	5,5	11,6	38	4,6	6,9
12,7	1/2	2,5	5,5	10,3	34	4,1	6,2
14,0	9/16	5,0	11,0	17,0	56	3,4	5,1
16,0	5/8	5,0	11,0	13,0	43	2,6	3,9
17,5	11/16	5,0	11,0	10,9	36	2,2	3,2
18,0	-	5,0	11,0	10,3	34	2,1	3,1
19,0	3/4	5,0	11,0	9,2	30	1,8	2,8
22,0	7/8	5,0	11,0	6,9	23	1,4	2,1
25,5	1	5,0	11,0	5,1	17	1,0	1,5

Packaging +/- 10 % in weight; Customized sizes and packaging are available on demand