






TECHNICAL DATA SHEET - CST 0280/02 - 24/06/2014

N3404

(*)				
T	°C	-100 +250		
p	bar		80	50
V	m/s		2	15
pH		2 + 12		

(*) Avoid the product's use at the maximum temperature and pressure associated values without consult the manufacturer

Average Composition

- Polyester synthetic fiber
- PTFE impregnation
- Lubricant silicon free

Features

N3404 packing is made with synthetic fiber impregnated with pure P.T.F.E. and an inert silicone free lubricant.

Applications

N3404 is designed for general services of dynamic applications.

sezione mm	sezione inch	kg/box	lbs/box	mt/box	ft/box	mt/kg	ft/lbs
3,0	1/8	1,0	2,2	85,5	280	85,5	127,3
4,0	-	1,0	2,2	48,1	158	48,1	71,6
5,0	3/16	1,0	2,2	30,8	101	30,8	45,8
6,0	-	2,5	5,5	53,4	175	21,4	31,8
6,5	1/4	2,5	5,5	45,5	149	18,2	27,1
8,0	5/16	2,5	5,5	30,0	99	12,0	17,9
9,5	3/8	2,5	5,5	21,3	70	8,5	12,7
10,0	-	2,5	5,5	19,2	63	7,7	11,5
11,0	7/16	2,5	5,5	15,9	52	6,4	9,5
12,0	-	2,5	5,5	13,4	44	5,3	8,0
12,7	1/2	2,5	5,5	11,9	39	4,8	7,1
14,0	9/16	5,0	11,0	19,6	64	3,9	5,8
16,0	5/8	5,0	11,0	15,0	49	3,0	4,5
17,5	11/16	5,0	11,0	12,6	41	2,5	3,7
18,0	-	5,0	11,0	11,9	39	2,4	3,5
19,0	3/4	5,0	11,0	10,7	35	2,1	3,2
22,0	7/8	5,0	11,0	7,9	26	1,6	2,4
25,5	1	5,0	11,0	5,9	19	1,2	1,8

(1) Packaging +/- 10 % in weight; Customized sizes and packaging are available on demand