







PL 5000L

				
T	°C	-200 +280		
p	bar		50	20
V	m/s		2	5
pH		0 + 14		



Avoid the product's use at the maximum temperature and pressure value associated without consult the manufacturer

Composition

White ePTFE yarns
Impregnation with silicon oil

Features

PL5000L is made by white ePTFE yarns silicon lubricated.

Applications

PL5000L is suitable for dynamic applications with slow motion pumps and mixers.

sezione mm	sezione inch	kg/box	lbs/box	mt/box	ft/box	mt/kg	ft/lbs
3,0	1/8	1,0	2,2	58,5	192	58,5	87,1
4,0	-	1,0	2,2	32,9	108	32,9	49,0
5,0	3/16	1,0	2,2	21,1	69	21,1	31,4
6,0	-	2,5	5,5	36,5	120	14,6	21,8
6,5	1/4	2,5	5,5	31,1	102	12,5	18,6
8,0	5/16	2,5	5,5	20,6	67	8,2	12,2
9,5	3/8	2,5	5,5	14,6	48	5,8	8,7
10,0	-	2,5	5,5	13,2	43	5,3	7,8
11,0	7/16	2,5	5,5	10,9	36	4,3	6,5
12,0	-	2,5	5,5	9,1	30	3,7	5,4
12,7	1/2	2,5	5,5	8,2	27	3,3	4,9
14,0	9/16	5,0	11,0	13,4	44	2,7	4,0
16,0	5/8	5,0	11,0	10,3	34	2,1	3,1
17,5	11/16	5,0	11,0	8,6	28	1,7	2,6
18,0	-	5,0	11,0	8,1	27	1,6	2,4
19,0	3/4	5,0	11,0	7,3	24	1,5	2,2
22,0	7/8	5,0	11,0	5,4	18	1,1	1,6
25,5	1	5,0	11,0	4,0	13	0,8	1,2

Packaged +/- 10 % in weight. Customized sizes and packaging are available on demand