







## PL 5000L

				
T	°C	-200    +280		
p	bar		50	20
V	m/s		2	5
pH		0 + 14		



Avoid the product's use at the maximum temperature and pressure value associated without consult the manufacturer

### Composition

White ePTFE yarns  
Impregnation with silicon oil

### Features

PL5000L is made by white ePTFE yarns silicon lubricated.

### Applications

PL5000L is suitable for dynamic applications with slow motion pumps and mixers.

sezione mm	sezione inch	kg/box	lbs/box	mt/box	ft/box	mt/kg	ft/lbs
3,0	1/8	1,0	2,2	58,5	192	58,5	87,1
4,0	-	1,0	2,2	32,9	108	32,9	49,0
5,0	3/16	1,0	2,2	21,1	69	21,1	31,4
6,0	-	2,5	5,5	36,5	120	14,6	21,8
6,5	1/4	2,5	5,5	31,1	102	12,5	18,6
8,0	5/16	2,5	5,5	20,6	67	8,2	12,2
9,5	3/8	2,5	5,5	14,6	48	5,8	8,7
10,0	-	2,5	5,5	13,2	43	5,3	7,8
11,0	7/16	2,5	5,5	10,9	36	4,3	6,5
12,0	-	2,5	5,5	9,1	30	3,7	5,4
12,7	1/2	2,5	5,5	8,2	27	3,3	4,9
14,0	9/16	5,0	11,0	13,4	44	2,7	4,0
16,0	5/8	5,0	11,0	10,3	34	2,1	3,1
17,5	11/16	5,0	11,0	8,6	28	1,7	2,6
18,0	-	5,0	11,0	8,1	27	1,6	2,4
19,0	3/4	5,0	11,0	7,3	24	1,5	2,2
22,0	7/8	5,0	11,0	5,4	18	1,1	1,6
25,5	1	5,0	11,0	4,0	13	0,8	1,2

Packaged +/- 10 % in weight. Customized sizes and packaging are available on demand