







TECHNICAL DATA SHEET - CST 0191/03 - 04/11/2013

PL 5000S

				
T	°C	-200 +280		
p	bar	300	100	
V	m/s	1	2	
pH		0 ÷ 14		



Avoid the product's use at the maximum temperature and pressure value associated without consult the manufacturer

Composition

ePTFE with yarns

Features

This packing is braided with white ePTFE yarns.

Applications

Packing suitable to seal the industrial valves, reciprocating pumps and mixer slow motion

sezione mm	sezione inch	kg/box	lbs/box	mt/box	ft/box	mt/kg	ft/lbs
3,0	1/8	1,0	2,2	61,7	203	61,7	91,9
4,0	-	1,0	2,2	34,7	114	34,7	51,7
5,0	3/16	1,0	2,2	22,2	73	22,2	33,1
6,0	-	2,5	5,5	38,6	127	15,4	23,0
6,5	1/4	2,5	5,5	32,9	108	13,1	19,6
8,0	5/16	2,5	5,5	21,7	71	8,7	12,9
9,5	3/8	2,5	5,5	15,4	50	6,2	9,2
10,0	-	2,5	5,5	13,9	46	5,6	8,3
11,0	7/16	2,5	5,5	11,5	38	4,6	6,8
12,0	-	2,5	5,5	9,6	32	3,9	5,7
12,7	1/2	2,5	5,5	8,6	28	3,4	5,1
14,0	9/16	5,0	11,0	14,2	46	2,8	4,2
16,0	5/8	5,0	11,0	10,9	36	2,2	3,2
17,5	11/16	5,0	11,0	9,1	30	1,8	2,7
18,0	-	5,0	11,0	8,6	28	1,7	2,6
19,0	3/4	5,0	11,0	7,7	25	1,5	2,3
22,0	7/8	5,0	11,0	5,7	19	1,1	1,7
25,5	1	5,0	11,0	4,3	14	0,9	1,3

Packaged +/- 10 % in weight. Customized sizes and packaging are available on demand