






TECHNICAL DATA SHEET - CST 0360/03 - 04/11/2013

**PT 5500 OX**

				
<b>T</b>	<b>°C</b>	<b>-200 +280</b>		
<b>p</b>	<b>bar</b>	<b>500</b>	<b>150</b>	
<b>V</b>	<b>m/s</b>	<b>1</b>	<b>2</b>	
<b>pH</b>		<b>0 + 14</b>		



Avoid the product's use at the maximum temperature and pressure value associated without consult the manufacturer

**SPECIAL PACKING FOR OXYGEN SERVICES**

**Composition**

Multifilament PTFE yarns for oxygen use

**Features**

This packing is manufactured using pure multifilament PTFE yarns.

**Applications**

PT5500 OX is particularly suitable oxygen services.

sezione mm	size inch	kg/box	lbs/box	mt/box	ft/box	mt/kg	ft/lbs
3,0	1/8	1,0	2,2	61,7	203	61,7	91,9
4,0	-	1,0	2,2	34,7	114	34,7	51,7
5,0	3/16	1,0	2,2	22,2	73	22,2	33,1
6,0	-	2,5	5,5	38,6	127	15,4	23,0
6,5	1/4	2,5	5,5	32,9	108	13,1	19,6
8,0	5/16	2,5	5,5	21,7	71	8,7	12,9
9,5	3/8	2,5	5,5	15,4	50	6,2	9,2
10,0	-	2,5	5,5	13,9	46	5,6	8,3
11,0	7/16	2,5	5,5	11,5	38	4,6	6,8
12,0	-	2,5	5,5	9,6	32	3,9	5,7
12,7	1/2	2,5	5,5	8,6	28	3,4	5,1
14,0	9/16	5,0	11,0	14,2	46	2,8	4,2
16,0	5/8	5,0	11,0	10,9	36	2,2	3,2
17,5	11/16	5,0	11,0	9,1	30	1,8	2,7
18,0	-	5,0	11,0	8,6	28	1,7	2,6
19,0	3/4	5,0	11,0	7,7	25	1,5	2,3
22,0	7/8	5,0	11,0	5,7	19	1,1	1,7
25,5	1	5,0	11,0	4,3	14	0,9	1,3

Packaged +/- 10 % in weight. Customized sizes and packaging are available on demand