







PT 5504AL

(*)				
T	°C	-200 +280		
p	bar		100	25
V	m/s		2	8
pH		0 + 14		



Avoid the product's use at the maximum temperature and pressure value associated without consult the manufacturer

Composition

Pure PTFE multifilament yarns
Impregnation with PTFE dispersion and lubricant
suitable for food and drug services

Features

PT5504AL, made by 100% PTFE multifilament yarns,
is lubricated with special compound, in order to reduce
the coefficient and guarantee long life services, suitable
for food and drug services.

Applications

PT5504AL is recommended for dynamic applications
with slow motion pumps and mixers for food and drug
services.

sezione mm	sezione inch	kg/box	lbs/box	mt/box	ft/box	mt/kg	ft/lbs
3,0	1/8	1,0	2,2	58,5	192	58,5	87,1
4,0	-	1,0	2,2	32,9	108	32,9	49,0
5,0	3/16	1,0	2,2	21,1	69	21,1	31,4
6,0	-	2,5	5,5	36,5	120	14,6	21,8
6,5	1/4	2,5	5,5	31,1	102	12,5	18,6
8,0	5/16	2,5	5,5	20,6	67	8,2	12,2
9,5	3/8	2,5	5,5	14,6	48	5,8	8,7
10,0	-	2,5	5,5	13,2	43	5,3	7,8
11,0	7/16	2,5	5,5	10,9	36	4,3	6,5
12,0	-	2,5	5,5	9,1	30	3,7	5,4
12,7	1/2	2,5	5,5	8,2	27	3,3	4,9
14,0	9/16	5,0	11,0	13,4	44	2,7	4,0
16,0	5/8	5,0	11,0	10,3	34	2,1	3,1
17,5	11/16	5,0	11,0	8,6	28	1,7	2,6
18,0	-	5,0	11,0	8,1	27	1,6	2,4
19,0	3/4	5,0	11,0	7,3	24	1,5	2,2
22,0	7/8	5,0	11,0	5,4	18	1,1	1,6
25,5	1	5,0	11,0	4,0	13	0,8	1,2

Packaged +/- 10 % in weight. Customized sizes and packaging are available on demand